

TIPO		POTENZA (P ₂)		Q m ³ /h l/min	0	1.5	3.0	6.0	9.0	12.0	15.0	16.5	18.0	21.0	24.0	27.0	30.0	33.0	
Monofase	Trifase	kW	HP		0	25	50	100	150	200	250	275	300	350	400	450	500	550	
DCm 8	DC 8	0.55	0.75	H metri	13	12.5	11.8	10.2	8.2	5.8	3								
DCm 10	DC 10	0.75	1		16	15.5	14.8	13.2	11.2	8.8	6	4.5	3						
DCm 20	DC 20	0.75	1		20	19	18.5	16.5	14.3	11.5	8								
DCm 30	DC 30	1.1	1.5		26	26	24.8	22	18.7	15	11	9							
DCm 42	DC 42	1.5	2		31	30.5	30	28.4	26.5	24.3	21.6	20.2	18.6	15.3	11.6	7.5	3		
DCm 43	DC 43	2.2	3		35.5	35	34.4	32.9	31	28.8	26.3	25	23.5	20.3	16.7	12.8	8.5	4	
-	DC 44	3	4		38	37.5	37	35.5	33.7	31.6	29.2	27.8	26.4	23.3	19.9	16.1	12	7.5	

Q = Portata H = Prevalenza manometrica totale

Tolleranza delle curve di prestazione secondo EN ISO 9906 Grado 3B.